



## MOVISTROB® Type 2000 N/S-EXT

A compact stroboscope with high light intensity and external triggering.

Order-No.: 1048

### GENERAL DATA

Light Source:	flash bulb, internal
Flash bulb:	socket-mounted Xenon-longlife, glass tube protected, model MS 2000, Order-No.: B10619
Light intensity:	max. 800 Lux at 50 Hz or approx. 400 Lux at 120 Hz in 50 cm distance from reflector (beam axis)
Flash duration:	approx. 2-7 $\mu$ s
Frequency range:	1-340 Hz = 60-20.400 RPM (min <sup>-1</sup> )
Trigger action:	external triggering -External control: TTL Signal, min. 5V-max. 24V

### TECHNICAL DATA

Power supply:	230V AC, 50 Hz / 115V AC on request
Housing:	shatterproof plastic, VDE-approved
Dimensions:	155 x 80 x 65 mm
Weight:	0,50 kg

### ADDITIONAL PRODUCTS

Adapter Type 900.01  
 Handlamp Type 900.00  
 Handlamp Type 900.02  
 Glass Fibre Optic Adapter Type 300.15  
 Magnifying Strob Lamp Type 900.06  
 Red Filter Type 500.11  
 Protective Spectacles incl. case Type 950.01  
 Telescopic Tripod Type 950.00  
 Carrying Case Type 300.10  
 Spare flash bulbs