



MOVISTROB® Type 2000-99 N

Minimum Size - Maximum Performance.

Order-No.: 1111

- very compact ministrobs with analog dial or LCD-display
- mains as well as battery operated Features
- Small dimensions, low weight, elegant and functional design
- trouble-free IC/CMOS-technology
- stabilized voltage, temperature constant
- precise fine adjustment of the flash frequency by rotary knob

GENERAL DATA

Light Source:	flash bulb, internal
Flash bulb:	socket mounted Xenon-longlife, model MS 2000, Art.No.: B10619
Light intensity:	max. 350 Lux in 50cm distance from reflector (beam axis)
Flash duration:	approx. 7 μ s
Frequency range:	2,5-300Hz = 150-18.000 RPM (min ⁻¹) subdivided into 2 overlapping ranges
Trigger action:	internal oscillator - Internal control: by dial potentiometer
Display:	reading in Hz (flashes per sec.) or RPM (min ⁻¹) by parallax-free scale setting.
Accuracy:	\pm 1% of the set value
Flash power control / range switching:	by change of frequency range via control push button

TECHNICAL DATA

Power supply:	115V AC, 50-60 Hz
Housing:	shatterproof plastic, VDE-approved
Dimensions:	155 x 80 x 65 mm
Weight:	approx. 0,6 kg

ADDITIONAL PRODUCTS

Adapter Type 900.01
 Handlamp Type 900.00
 Handlamp Type 900.02
 Glass Fibre Optic Adapter Type 300.15
 Magnifying Strob Lamp Type 900.06
 Red Filter Type 500.11
 Protective Spectacles incl. case Type 950.01
 Telescopic Tripod Type 950.00
 Carrying Case Type 300.10
 Spare flash bulbs