BBE



MOVISTROB® Type 3000 N/D

Ergonomically styled small size stroboscope with LC-display and maximum performance.

Order-No.: 3114

Very compact, ergonomically styled, processor-controlled ministroboscope with LC-display and mains-operation.

- small dimensions, low weight
- innovative and elegant design
- trouble-free processor-technology
- standby with data-hold function (last measured value will be stored), restart by tipping encoder, very precise fine adjustment of the flash frequency by encoder with cursor shifting
- stabilized voltage, temperature constant

GENERAL DATA

Light Source: flash bulb, internal

Flash bulb: socket mounted Xenon-longlife,

model MS 2000, Art.No.: B10619

Light intensity: max. 450 Lux in 50cm distance from

reflector (beam axis)

Flash duration: approx. 2-7µs

Frequency range: $0.5-335 \text{ Hz} = 30-20.100 \text{ RPM (min}^{-1})$

with automatic flash power control

Trigger action: internal oscillator

- Internal control: by rotary pulse encoder

cursor control by "Push&Turn", Standby with data-hold function

(after 5 minutes), last value will be stored

Display: LC-display with 2 x 8 characters,

can be switched to Hz (flashes per sec.)

or RPM (min-1) reading

Memory: last set value

Accuracy: < 0,02% of the set value (f / Hz)

(quarz timing)

Flash power control /

range switching: automatically

TECHNICAL DATA

Power supply: 220V-250V AC, 50-60 Hz

Housing: ergonomically styled industrial design,

shatterproof plastic, VDE-approved

Dimensions: 155 x 95 x 85 mm Weight: approx. 0,6 kg

ADDITIONAL PRODUCTS

Adapter Type 900.01 Handlamp Type 900.00 Handlamp Type 900.02

Glass Fibre Optic Adapter Type 300.15 Magnifying Strob Lamp Type 900.06

Red Filter Type 500.11

Protective Spectacles incl. case Type 950.01

Telescopic Tripod Type 950.00 Carrying Case Type 300.10

Spare flash bulbs

NOTICE

Special models with higher light intensity (600 Lux max.) or increased frequency range (up to 30.000 RPM) on request.

Internal control / trigger action without standby

on request (constant power).

Further special modifications on request.