



## MOVISTROB® Type 3000 B/A

Ergonomically styled small size stroboscope with one hand operation and maximum performance.

Order-No.: 3118

- small dimensions, low weight
- innovative and elegant design,
- trouble-free processor-technology,
- very precise adjustment of the flash frequency by rotary knob scale
- stabilized voltage, temperature constant

## GENERAL DATA

Light Source:	flash bulb, internal
Flash bulb:	socket mounted Xenon-longlife, model MS 2000, Art.No.: B10619
Light intensity:	max. 450 Lux in 50cm distance from reflector (beam axis)
Flash duration:	approx. 2-7µs
Frequency range:	2,5-300Hz = 150-18.000 RPM (min <sup>-1</sup> ) subdivided into 2 overlapping ranges 1.) 2,5-66,6 Hz = 150-4000 RPM (min <sup>-1</sup> ) 2.) 61,6-300 Hz = 3700-18000 RPM (min <sup>-1</sup> )
Trigger action:	internal oscillator - Internal control: by dial potentiometer
Display:	reading in Hz (flashes per sec.) or RPM (min <sup>-1</sup> ) by parallax-free scale setting
Accuracy:	± 2% of the set value
Flash power control / range switching:	by change of frequency range via control push button

## TECHNICAL DATA

Power supply:	12V DC, Power consumption: 1,7A
Housing:	ergonomically styled industrial design, shatterproof plastic, VDE-approved
Dimensions:	155 x 95 x 85 mm
Weight:	approx. 0,450 kg

## ADDITIONAL PRODUCTS

Adapter Type 900.01  
Handlamp Type 900.00  
Handlamp Type 900.02  
Glass Fibre Optic Adapter Type 300.15  
Magnifying Strob Lamp Type 900.06  
Red Filter Type 500.11  
Protective Spectacles incl. case Type 950.01  
Telescopic Tripod Type 950.00  
Carrying Case Type 300.10  
Spare flash bulbs

## NOTICE

Very compact, ergonomically styled, processor-controlled ministroboscope with analogue dial and external powerpack operation.

- Powerpack 2020.03 optional