



MOVISTROB® TYP 2000-99 N

Art.No.:2110 (230V AC) | Art.No.:1111 (115V AC)

Power giant in pocket format

Compact, processor-controlled mini stroboscope with analog display and mains operation.

Advantages: Small dimensions, low weight, elegant as well as practical industrial form, interference-resistant processor technology, voltage-stabilized, temperature-constant, exact fine adjustment of the flash frequency via rotary knob.



GENERAL DATA

Light Source:	flash bulb, internal
Flash bulb:	socket mounted Xenon-Longlife
Light intensity:	max. 450 Lux in 50 cm distance from reflector (beam axis)
Flash duration:	approx. 2 - 7 μ s
Frequency range:	2,5 - 300Hz = 150 - 18.000 U/min subdivided into 2 overlapping ranges 1.) 2,5 - 66,6 Hz = 150 - 4000 RPM (min-1) 2.) 61,6 - 300 Hz = 3700 - 18000 RPM (min-1)
Trigger action:	internal oscillator
Display:	in Hz / flashes and U/min / RPM by anti-parallax scale
Accuracy:	\pm 2% of the set value
Flash power control:	by change of frequency range via control push button

SPECIAL DATA

Power supply:	220V - 250V AC, 50-60 Hz oder 115V AC, 50-60 Hz
Power consumption:	0,3A / 0,5A
Housing:	ergonomically styled industrial design, shatterproof plastic, VDE-approved
Dimensions:	155 x 95 x 85 mm
Weight:	ca. 0,6 kg

ACCESSORIES

Red Filter Type 2000.11
Protective Spectacles incl. case Type 950.01
Carrying Case Type 3000.10
Spare flash bulbs