



MOVISTROB® TYP 3000 N/A-S

Art.No.:3109 (230V AC)

**Ergonomically styled small size
stroboscope with one hand operation
and maximum performance.**

Very compact, ergonomically styled
processor-controlled ministroboscope with
analogue dial and mains-operation.
-small dimensions, low weight

- innovative and elegant design
- trouble-free processor-technology
- very precise adjustment of the flash
frequency by rotary knob scale
- stabilized voltage, temperature constant



GENERAL DATA

Light Source:	flash bulb, internal
Flash bulb:	socket-mounted Xenon-Longlife
Light intensity:	max. 600 Lux in 50 cm distance from reflector (beam axis)
Flash duration:	approx. 2 - 7µs
Frequency range:	2,5 - 300Hz = 150 - 18.000 U/min subdivided into 2 overlapping ranges
Trigger action:	internal oscillator
-Internal control:	internal control: by dial potentiometer
Display:	reading in HZ or RPM by parallax-free scale setting
Accuracy:	± 2% of the set value
Flash power control:	by change of frequency range via control push button

SPECIAL DATA

Power supply:	220V - 250V AC, 50-60 Hz
Power consumption:	0,3A / 0,5A
Housing:	ergonomically styled industrial design, shatterproof plastic, VDE-approved
Dimensions:	155 x 95 x 85 mm
Weight:	ca. 0,6 kg

ACCESSORIES

Red Filter Type 2000.11
Protective Spectacles incl. case Type 950.01
Carrying Case Type 3000.10
Spare flash bulbs