



# MOVISTROB® TYP 3000 N/A

Art.No.:3110 (230V AC) | Art.No.:3111 (115V AC)

**Ergonomically styled small size  
stroboscope with one hand operation  
and maximum performance**

Very compact, ergonomically styled processor-controlled ministroboscope with analogue dial and mains-operation.

Features: Small dimensions, low weight, innovative and elegant design, trouble-free processor-technology, very precise adjustment of the flash frequency by rotary knob scale, stabilized voltage, temperature constant



## GENERAL DATA

Light Source:	flash bulb, internal
Flash bulb:	socket mounted Xenon-Longlife
Light intensity:	max. 450 Lux in 50 cm distance from reflector (beam axis)
Flash duration:	approx. 2 - 7µs
Frequency range:	2,5 - 300Hz = 150 - 18.000 U/min subdivided into 2 overlapping ranges 1.) 2,5 - 66,6 Hz = 150 - 4000 RPM (min-1) 2.) 61,6 - 300 Hz = 3700 - 18000 RPM (min-1)
Trigger action:	internal oxcillator
Display:	in HZ / flashes and U/min / RPM by anti-parallax scale
Accuracy:	± 2% of the set value
Flash power control:	by change of frequency range via control push button

## SPECIAL DATA

Power supply:	220V - 250V AC, 50-60 Hz oder 115V AC, 50-60 Hz
Power consumption:	0,3A / 0,5A
Housing:	ergonomically styled industrial design, shatterproof plastic, VDE-approved
Dimensions:	155 x 95 x 85 mm
Weight:	ca. 0,6 kg

## ACCESSORIES

Red Filter Type 2000.11  
Protective Spectacles incl. case Type 950.01  
Carrying Case Type 3000.10  
Spare flash bulbs