



MOVISTROB® TYP 3000 N/D

Art.No.:3114 (230V AC) | Art.No.:3115 (115V AC)

Ergonomically styled small size stroboscope with maximum performance

Very compact, ergonomically styled processor-controlled ministroboscope with LC-display and mains-operation

Features:

Small dimensions, low weight, innovative and elegant design, trouble-free processor-technology, standby with data-hold function (last measured value will be stored), restart by tipping the encoder, very precise fine adjustment of the flash frequency by encoder with cursor shifting, stabilized voltage, temperature constant



GENERAL DATA

Light Source:	flash bulb, internal
Flash bulb:	socket-mounted Xenon-Longlife
Light intensity:	max. 450 Lux in 50 cm distance from reflector (beam axis)
Flash duration:	approx. 2 - 7µs
Frequency range:	0.5 - 335 Hz = 30 - 20.100 U/min with automatic flash power control
Trigger action:	internal oscillator
-Internal control:	by rotary pulse encoder, cursor control by "Push&Turn", Standby with data-hold function (after 5 minutes), last value will be stored
Display:	LC-Display mit 2 x 8 Characters, umschaltbar in Hz oder RPM (min-1)
Accuracy:	< 0,02% of the set value (quarz timing)
Flash power control:	automatically

SPECIAL DATA

Power supply:	220V - 250V AC, 50-60 Hz oder 115V AC, 50-60 Hz
Power consumption:	0,3A / 0,5A
Housing:	ergonomically styled industrial design, shatterproof plastic, VDE-approved
Dimensions:	155 x 95 x 85 mm
Weight:	ca. 0,6 kg

ACCESSORIES

Red Filter Type 2000.11
Protective Spectacles incl. case
Type 950.01
Carrying Case Type 3000.10
Spare flash bulbs

NOTICE

Special models with higher light intensity (600 Lux max.) or increased frequency range (up to 30.000 RPM) on request.
Internal control / trigger action without standby on request (constant power).