



# MOVISTROB® TYP 3000 B/D

Art.No.:3119 (12V DC)

## Ergonomically styled small size stroboscope with LC-display and maximum performance

Very compact, ergonomically styled processor-controlled ministroboscope with LC-display and external power pack operation.  
(power pack 2020.03 optional)

Features:

Small dimensions, low weight, innovative and elegant design, trouble-free processor technology, Standby with data-hold function (last measured value will be stored), restart by tipping the encoder, very precise fine adjustment of the flash frequency by encoder with cursor shifting, stabilized voltage, temperature constant.



## GENERAL DATA

Light Source:	flash bulb, internal
Flash bulb:	socket-mounted Xenon-longlife
Light intensity:	max. 450 Lux in 50 cm distance from reflector (beam axis)
Flash duration:	approx. 2 - 7µs
Frequency range:	0.5 - 335 Hz = 30 - 20.100 U/min with automatic flash power control
Trigger action:	internal oscillator
-Internal control:	by rotary pulse encoder, cursor control by "Push&Turn", Standby with data-hold function (after 2 min.)
Display:	LC-Display with 2 x 8 Characters, can be switched to Hz oder RPM (min-1)
Accuracy:	< 0,02% of the set value (quarz timing)
Flash power control:	automatically

## SPECIAL DATA

Power supply:	12V DC
Ppower consumption:	max. 1,7A
Housing:	ergonomically styled industrial design, shatterproof plastic, VDE-approved
Dimensions:	155 x 95 x 85 mm
Weight:	ca. 0,450 kg

## ACCESSORIES

Accupack Type 2020.03  
Red Filter Type 2000.11  
Protective Spectacles  
incl. Case Type 950.01  
Carrying Case Type 3000.10  
Spare flash bulbs

## NOTICE

Recommended accessory: Power Pack Type 2020.03  
Special models with higher light intensity (600 Lux max.) or increased frequency range (up to 30.000 RPM) on request.  
Internal control / trigger action without standby on request (constant power).